



**INDUSTRIAL
CHOICE**



Engineered Hose Solutions

Fuel Oil Delivery Hose

INDUSTRIAL CHOICE FUEL OIL DELIVERY 1" (25,4mm) 250 PSI WP MADE IN SPAIN



Tube: Nitrile Rubber Class A, W/Anti static (R < 108U)

Reinforcement: 2 Kevlar Spiral Braids.

Cover Smooth NBR/PVC Class A, Blend for Durability.

Designed for Transfer/Delivery of Fuels & Oils : Gasoline, Diesel, Bio-Diesel B20, Kerosene, Hyd Oils & Related Petro-based products.

250 WPSI. -40F to 212F. Great for Mounting on Hose Reels.

Warnings: Gasoline and other high Aromatic fuels should not be conveyed at higher than 130F!

Warnings: The user of this product is responsible for determining if the hose is suitable for the application!

1 piece Long length Rolls! = Less Remnants = Less Waste

Part #	O.D.	WPSI	Bend Radius	Weight Ft.		
ICH-FOD-1-410'	1.51"	250	6.5	.65lbs/ft		
ICH-FOD-1.25-330'	1.81"	250	8.5	.80lbs/ft		
ICH-FOD-1.38-315'	1.915"	250	9.0	.85lbs/ft		
ICH-FOD-1.5-300'	2.08"	250	10	1.01lbs/ft		

Note! Dimensions and weights can vary slightly and are approximate!



**INDUSTRIAL
CHOICE**