



INDUSTRIAL CHOICE



INDUSTRIAL CHOICE DURAGLIDE FUEL DROP HOSE 353

CORRUGATED REINFORCED RUBBER LIGHTWEIGHT FUEL DROP HOSE W/EXPOSED HELIX



DuraGlide 353 Fuel Drop Hose is an engineered hose, specially compounded to make it Durable, Easy to Drag, Flexible & Lightweight. It pulls a Full Vacuum/Suction (30" Hg). Designed for both drop and 150WPSI Pump off service. Handles gasoline grades to 50% aromatic, Bio fuels to B20 like biodiesel & biogasoline blends plus most refined oils. Internal static wire assures no static build up if properly grounded. See Guidelines Use on Transport Trucks, Trailers and in-Plant loading and Transferring!

Item Number	ID (Inch)	OD (Inch)	WPSI	Bend Radius	Weight (lbs/ft.)	Notes
FDH-DG353-2	2	2.95	150	4	1.230	
FDH-DG353-3	3	3.96	150	7	1.750	
FDH-DG353-4	4	4.94	150	10	2.300	

Note! Dimensions and weights can vary slightly and are approximate!

Tube: Black Nitrile Rubber blend, antistatic (R<108Ω)

Cover: Black Nitrile Rubber blend W/Exposed PVC proprietary blended helix provides abrasion resistance, durability and ease of pulling over rough surfaces.

Reinforcement: Multiple Ply Textile Spirals W/internal static wire.

Temperatures: -40F to 150F. Note PSI ratings at 78F as Temp's go up Wpsi goes down.

Warning: The user of this product is responsible for determining if the hose is suitable for the application!

Warning: Attaching hose ends W/bands or clamps may reduce hose assembly WPSI. See Nahad Guidelines.

Compare to: Parker/Titan 353, Contitech Infinity Fuel Drop Hose.